


**Kompakt ENA 36**



**Rugged**

- Ensures long service life and reliability of the application, no wear  
Non-contact measuring system
- Stays sealed even when subjected to harsh everyday use. Offers security against failures in the field  
Solid die-cast housing with up to IP 69K protection
- Can be used for a wide temperature range without additional expense.  
Wide temperature range (-40 °C ... +85 °C)
- Increased ability to withstand vibration and installation errors. Eliminates machine downtime and repairs.  
High shock resistance (> 500g) and vibration resistance (>30g)
- Can be used in outdoor applications with large fluctuations in temperature.  
Resistant against humidity and condensation.



**Compact**

- Can be used where space is tight  
Overall diameter of only 36 mm
- Compact encoder, suitable for large shafts  
Blind hollow shaft up to 10 mm, shaft up to 6,35 mm

**Versatile**

- Interface: 9-Bit SSI, 4 ... 20 mA, 0 ... 10 V  
One size available for different applications
- Measuring range: 45°; 90°; 180°; 360°:  
Suitable measuring range available for different applications
- Enables simple installation  
Reference point can be identified via LED (green)
- Easy diagnosis in case of fault condition  
Error indication via LED (red)
- Individual fixing can be implemented  
Torque stop slot and synchro flange available


**Mechanical characteristics:**

Max. speed:	6000 min <sup>-1</sup>
Starting torque	< 0,06 Nm
Weight:	approx. 0,2 kg
Protection acc. to EN 60 529:	IP 67 (IP 69k on request)
Working temperature:	-40 °C ... +85 °C
Materials:	Shaft: stainless steel, Flange: aluminium, Housing: die cast zinc, Cable: PUR
Shock resistance acc. to DIN-IEC 68-2-27:	5000 m/s <sup>2</sup> , 6 ms
Vibration resistance acc. to DIN-IEC 68-2-6:	300 m/s <sup>2</sup> , 10 ... 2000 Hz
Permanent shock resistance acc. to DIN-IEC 68-2-29	1000 m/s <sup>2</sup> , 2 ms
Vibration (broad-band random) to DIN-IEC 68-2-64	5 ... 2500 Hz, 100 m/s <sup>2</sup> - rms

All-round protection thanks to **Safety-Lockplus™** and **Sensor-Protect™** technology

**Safety-Lockplus™:**

IP69k protection on the flange side, robust bearing assemblies with interlocking bearings, mechanically protected shaft seal



**Sensor-Protect™:**

Fully encapsulated electronics, separate mechanical bearing assembly

**Kompakt ENA 36**

**Electrical characteristics SSI Interface:**

<b>Sensor:</b>	
Supply voltage:	5 ... 30 V DC <sup>1)</sup>
Current consumption (w/o output load):	typ 22 mA, max. 41 mA
Reverse polarity protection at power supply (Ub):	Yes
Measuring range:	360°
Resolution/Code:	9 Bit/Binary
Linearity (25 °C)	<1.0 %
Repeat accuracy:	<0.2 %
Data refresh rate:	typ 100 µs
Status LED:	Green, reference point at 2,1°

<b>SSI interface</b>	
Clock speed:	100 kHz ... 750 kHz
Output driver:	RS 485
Monoflop time typ./max.:	16 µs/20 µs
Short circuit proof outputs:	Yes <sup>2)</sup>
Permissible load/channel	typ. 120 Ohm (corresponding RS 485)

- <sup>1)</sup> The supply voltage at the encoder input must not be less than 4.75 V (5 V - 5%)  
<sup>2)</sup> Short circuit to 0V or to output, only one channel at a time, supply voltage correctly applied

**Terminal assignment:**


<b>Sig.:</b>	0V	+Ub	0 V Sens	+Ub Sens	+T	-T	+D	-D
<b>Col.:</b>	WH	BN	BU	RD	GN	YE	GY	PK

**Electrical characteristics current interface 4 ... 20 mA:**

<b>Sensor:</b>	
Supply voltage:	18 ... 30 V DC
Current consumption (w/o output load):	typ 25 mA, max. 42 mA
Reverse polarity protection at power supply (Ub):	Yes
Measuring range:	45°, 90°, 180° or 360° (see also table „measuring range“)
Linearity (25 °C)	<1.0 % (360 ° measurement range)
Repeat accuracy:	<0.2 % (360 ° measurement range)
Status LED:	Green: reference point at 2.1° Red: sensor break detection , Control power supply

<b>4 ... 20 mA current loop</b>	
Output load:	max. 500 ohms at 24 V DC
Setting time:	< 1 ms (R <sub>load</sub> = 400 Ohm, 25 °C)
Short-circuit proof outputs: when the supply voltage is correctly applied, then output to output is short-circuit protected. But not output to 0 V or to +Ub	
Supply voltage and sensor output signal are not galvanically isolated.	

**Example (output signal profile):**



**Terminal assignment:**

<b>Sig.:</b>	0V	+Ub	+I	-I
<b>Col.:</b>	WH	BN	GN	YE


**Electrical characteristics voltage interface 0 ... 10 V:**

<b>Sensor:</b>	
Supply voltage:	20 ... 30 V DC
Current consumption: (w/o output load):	typ 27 mA, max. 47 mA
Reverse polarity protection at power supply (Ub):	Yes
Measuring range:	45°, 90°, 180° or 360° (see also table „measuring range“)
Linearity(25 °C)	<1.0 % (360 ° measurement range)
Repeat accuracy:	<0.2 % (360 ° measurement range)
Status LED:	Green: reference point at 2.1°

<b>0 ... 10 V voltage output</b>	
Current output:	max. 10 mA
Setting time:	< 1 ms (R <sub>last</sub> = 1 KOhm, 25 °C)
Short-circuit proof outputs:	Yes <sup>2)</sup>
Supply voltage and sensor output signal are not galvanically isolated.	

- <sup>2)</sup>Short circuit to 0V or to output, only one channel at a time, supply voltage correctly applied

**Example (output signal profile):**



**Terminal assignment:**

<b>Sig.:</b>	0V	+Ub	+U <sub>0</sub>	-U <sub>0</sub>
<b>Col.:</b>	WH	BN	GN	YE


**General characteristics:**

Conforms to CE requirements acc. to EN 61000-6-1, EN 61000-6-4, EN 61000-6-3 and EN 61000-4-8 (behaviour under magnetic influence).

**Kompakt ENA 36**


Dimensions

ø 36 mm, Flange with long torque stop



1 Torque stop slot,  
Recommendation: cyl. pin. acc. DIN 7 Ø4

ø 36 mm, Synchro flange



**Kompakt ENA 36**

Order code:

ENA 36 . X X X X . X X X X

- Type
- Flange  
 2 = Flange with long torque stop  
 5 = Flange with stator coupling
- Hollow shaft  
 2 = ø 6 mm  
 3 = ø 6,35 (1/4")  
 4 = ø 8 mm  
 6 = ø 10 mm
- Output circuit / Power supply  
 2 = SSI/5 ... 30 V DC  
 3 = 4 ... 20 mA/18 ... 30 V DC  
 4 = 0 ... 10 V DC/20 ... 30 V DC

- Option 1  
 1 = IP 67 (IP 69k on request)
- Option 2  
 1 = Count direction cw\*  
 2 = Count direction ccw\*
- Code type and division  
 use corresponding table
- Type of connection  
 2 = Cable radial (1 m PUR)

\*cw = increasing code values when shaft turning clockwise (cw). Top view on shaft.

**Code type and division:**

**SSI interface**  
 B9 = 9 Bit binary

**Current interface 4 ... 20 mA**  
 45 = 45° measurement range  
 90 = 90° measurement range  
 18 = 180° measurement range  
 36 = 360° measurement range

**Voltage interface 0 ... 10 V**  
 45 = 45° measurement range  
 90 = 90° measurement range  
 18 = 180° measurement range  
 36 = 360° measurement range

**Measuring range:**

Measuring range:	360°	180°	90°	45°
Internal resolution (Measuring range):	9 Bit 512 steps	8 Bit 256 steps	7 Bit 128 steps	6 Bit 64 steps
Interfaces:	SSI	–	–	–
	4 ... 20 mA	4 ... 20 mA	4 ... 20 mA	4 ... 20 mA
	0 ... 10 V	0 ... 10 V	0 ... 10 V	0 ... 10 V